



Product Application Guide¹ (Gallons per 100 SF)

	Smooth BUR/MB ²	Granule BUR/MB ²	Recoat Existing <small>Acrylic Coated</small>	Metal Roofs	Metal Walls	Masonry/ EFIS/Concrete Walls	Sealing Brick/Block Walls
Primer M-800 Metal Rust Inhibitor WC-900 Wall Primer (Clear)				.33 to .5	0.5	0.25	
Base Coat M-200 Gray Base Coat (Aged) M-700 Gray Base Coat (New) WC-190 Wall Coating WC-300 Clear Wall Sealer	0.75 0.75	1.00 1.00	1.00	1.00	0.50	1.00	.25-.33
Finish Coat M-100 Coating WC-190 Wall Coating WC-300 Clear Wall Sealer	1.25	1.25	1.00	1.25	0.75	1.00	.25-.33

¹ This guide provides approximate product usage per 100 SF based on MEGA Guide Specifications. Application rates may vary by specific projects, climates and/or job conditions. An adhesion test to all surfaces is required unless waived in writing by MEGA. All surfaces to be coated must be properly cleaned prior to the application of products per MEGA Guide Specifications.

² Excludes aluminum coated surfaces, coal tar systems, silicone and Kynar surfaces. Contact MEGA.